

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2023

Version number 2 (replaces version 1)

Revision: 17.08.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name **weberfloor 4670N Marine Base**

Safety data sheet no.: XXP013471

UFI: Q580-E0GH-W00K-FCY8

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

**Application of the substance / the mixture** Floor screed - fast cement

#### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

Saint-Gobain Byggevarer as  
Sandstuveien 68  
Postboks 6211 Etterstad  
0603 Oslo  
Norway

Phone: +47 41 63 50 46

teknisk@weber-norge.no

#### 1.4 Emergency telephone number:

GIFTINFORMASJONSSENTRALEN (Norwegian Poison Information Centre): +47 22 59 13 0

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

Results of in vitro- tests have shown that cement based mixtures with more than 1% of cement cause serious skin irritation and serious eye damage, therefore the classification of these mixtures regarding H315 and H318 is not based on the calculation of the ingredients or the pH in this case.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

#### 2.2 Label elements

##### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

##### Hazard pictograms



GHS05

**Signal word** Danger

(Contd. on page 2)

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2023

Version number 2 (replaces version 1)

Revision: 17.08.2023

**Trade name weberfloor 4670N Marine Base**

(Contd. of page 1)

**Hazard-determining components of labelling:**

cement portland, grey

**Hazard statements**

H315 Causes skin irritation.

H318 Causes serious eye damage.

**Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

Contains portland cement with a soluble chromium VI content under 2 ppm during the conservation period indicated on the packaging.

EUH208 Contains cement portland, grey. May produce an allergic reaction.

**2.3 Other hazards**

Product mixed with water gives a pH between 10.5 and 11.5.

The product contains silica sand with less than 1% of fine fraction and therefore is not classified as hazardous; however, pay attention when handling and follow the indications relating to personal protective equipment.

**Results of PBT and vPvB assessment**

**PBT:** Does not contain PBT substances.

**vPvB:** Does not contain vPvB substances.

**SECTION 3: Composition/information on ingredients**

**3.2 Mixtures**

**Description:** Mixture consisting of the following components.

**Dangerous components:**

CAS: 14808-60-7 EINECS: 238-878-4	Silicon dioxide (Quartz sand) substance with a Community workplace exposure limit	70-90%
CAS: 7778-18-9 EINECS: 231-900-3 Reg.nr.: 01-2119444918-26-xxxx	calcium sulphate, different hydrate levels CaSO <sub>4</sub> x n H <sub>2</sub> O (n = 0; 1/2; 2) substance with a Community workplace exposure limit	2-5%
CAS: 471-34-1 EINECS: 207-439-9 Reg.nr.: 01-2119486795-18-xxxx	calcium carbonate substance with a Community workplace exposure limit	2-5%
CAS: 65997-15-1 EINECS: 266-043-4	cement portland, grey ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335, EUH203 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 1 % Eye Dam. 1; H318: C ≥ 1 %	2-5%

(Contd. on page 3)

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2023

Version number 2 (replaces version 1)

Revision: 17.08.2023

**Trade name weberfloor 4670N Marine Base**

(Contd. of page 2)

**SVHC** Void**Additional information**

The mixture is "low chromate" according to the Regulation (EC) No 1272/2008 within the product shelf-life, so that the classification with H317 is not applicable, when the packing was not opened in the meantime.

For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

**4.1 Description of first aid measures****General information**

Immediately remove any clothing soiled by the product.

Remove the victim immediately from the danger area. If the patient is unwell consult a doctor and present this data sheet.

**After inhalation** Supply fresh air; consult doctor in case of complaints.

**After skin contact** Immediately rinse with water.

**After eye contact**

Rinse opened eye for several minutes under running water. Rinse liquid should be tempered (20-30°C). Seek immediate medical advice.

**After swallowing**

Rinse out mouth with water. Do not induce vomiting. Seek medical attention and present this data sheet.

**4.2 Most important symptoms and effects, both acute and delayed**

This powder (wet or dry) may cause irritation or potentially irreversible serious injury on contact with the eyes. Prolonged contact with moist skin (due to e.g. sweat or humidity) can cause skin irritation

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### SECTION 5: Firefighting measures

**5.1 Extinguishing media****Suitable extinguishing agents**

The product is not combustible.

Use fire extinguishing methods suitable to surrounding conditions.

**5.2 Special hazards arising from the substance or mixture** No further relevant information available.

**5.3 Advice for firefighters**

**Protective equipment:** Use methods suitable to surrounding conditions.

### SECTION 6: Accidental release measures

**6.1 Personal precautions, protective equipment and emergency procedures**

Avoid formation of dust.

Ensure adequate ventilation.

**6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course.

**6.3 Methods and material for containment and cleaning up:**

The dry powder and the fresh product is removed with water. The hardened product is removed mechanically.

(Contd. on page 4)

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2023

Version number 2 (replaces version 1)

Revision: 17.08.2023

**Trade name weberfloor 4670N Marine Base**

(Contd. of page 3)

### 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Avoid contact with skin and eyes.

Prevent formation of dust.

Provide suction extractors if dust is formed.

**Information about fire - and explosion protection:** No special measures required.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage

**Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.

**Information about storage in one common storage facility:** Store away from foodstuffs.

#### Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from humidity and water.

Cr(VI) reducing agent efficiency: the integrity of the packaging and the compliance with the above mentioned storage conditions are essential conditions to ensure the effectiveness of the reducing agent for the period of time indicated on each individual bag, or for three months from the delivery date for the bulk product (see Section 15).

**7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

**Ingredients with limit values that require monitoring at the workplace:**

DNELs		
<b>CAS: 65997-16-2 Cement, alumina, chemicals</b>		
Inhalative	Derived No Effect Level	2.5 mg/m <sup>3</sup> (worker systemic long term value) 5 mg/m <sup>3</sup> (worker systemic short term value)
<b>CAS: 7778-18-9 calcium sulphate, different hydrate levels CaSO<sub>4</sub> x n H<sub>2</sub>O (n = 0; 1/2; 2)</b>		
Oral	Derived No Effect Level	1.52 mg/kgxday (consumer systemic long term value) 11.4 mg/kgxday (consumer systemic short term value)
Inhalative	Derived No Effect Level	21.17 mg/m <sup>3</sup> (worker systemic long term value) 5,082 mg/m <sup>3</sup> (worker systemic short term value) 5.29 mg/m <sup>3</sup> (consumer systemic long term value) 3,811 mg/m <sup>3</sup> (consumer systemic short term value)
<b>CAS: 471-34-1 calcium carbonate</b>		
Inhalative	Derived No Effect Level	6.36 mg/m <sup>3</sup> (worker local long term value) 1.06 mg/m <sup>3</sup> (consumer local long term value)

(Contd. on page 5)

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2023

Version number 2 (replaces version 1)

Revision: 17.08.2023

**Trade name weberfloor 4670N Marine Base**

(Contd. of page 4)

CAS No. / Designation of material / % / Type / Value / Unit	
<b>CAS: 14808-60-7 Silicon dioxide (Quartz sand)</b>	
BOELV (European Union)	Long-term value: 0.1* mg/m <sup>3</sup> *respirable fraction
MAK (Germany)	Long-term value: 0.05 mg/m <sup>3</sup> alveolengängige Fraktion
GV (Denmark)	Short-term value: 0.6* 0.2** mg/m <sup>3</sup> Long-term value: 0.3* 0.1** mg/m <sup>3</sup> *total; **total, respirabel: K
LEP (Spain)	Long-term value: 0.05 mg/m <sup>3</sup> *Fracción resp:n,d,y
TWA (Italy)	Long-term value: 0.025 mg/m <sup>3</sup> A2, (j)
VLE (Portugal)	Long-term value: 0.05 mg/m <sup>3</sup> Resp.;A2; fibrose pulmonar; cancro do pulmão
OEL (Sweden)	Long-term value: 0.1 mg/m <sup>3</sup> C, M, respirabel fraktion
HTP (Finland)	Long-term value: 0.05 0.1* mg/m <sup>3</sup> alveolijae;*sitovat raja-arvot, pöly
<b>CAS: 7778-18-9 calcium sulphate, different hydrate levels CaSO<sub>4</sub> x n H<sub>2</sub>O (n = 0; 1/2; 2)</b>	
AGW (Germany)	Long-term value: 6 A mg/m <sup>3</sup> DFG
LEP (Spain)	Long-term value: 10 mg/m <sup>3</sup> e
TWA (Italy)	Long-term value: 10 mg/m <sup>3</sup> (i)
VLE (Portugal)	Long-term value: 10 mg/m <sup>3</sup> Fração inalável; Sintomas nasais
<b>CAS: 471-34-1 calcium carbonate</b>	
LEP (Spain)	Long-term value: 10 mg/m <sup>3</sup>
TWA (Italy)	Long-term value: (10) mg/m <sup>3</sup> (e)
VLE (Portugal)	Long-term value: (10) mg/m <sup>3</sup> (Irritação)
<b>CAS: 65997-15-1 cement portland, grey</b>	
AGW (Germany)	Long-term value: 5 E mg/m <sup>3</sup> DFG
LEP (Spain)	Long-term value: 4 mg/m <sup>3</sup> fracción respirable: e, d
TWA (Italy)	Long-term value: 1 mg/m <sup>3</sup> (e, j), A4
VLE (Portugal)	Long-term value: 1 mg/m <sup>3</sup> Fração resp.;A4,função pulm.,sintomas resp.,asma
HTP (Finland)	Long-term value: 5* 1** mg/m <sup>3</sup> *hengittyvä pöly, **alveolijae

(Contd. on page 6)

EUG

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2023

Version number 2 (replaces version 1)

Revision: 17.08.2023

Trade name weberfloor 4670N Marine Base

(Contd. of page 5)

### Additional Occupational Exposure Limit Values for possible hazards during processing:

Total inhalable dust: 10 mg/m<sup>3</sup>

Respirable dust (< 5 µm): 4 mg/m<sup>3</sup>

Quartz respirable dust (< 5 µm) : 0,15 mg/m<sup>3</sup>

### Additional information:

The applicable TRGS 900 (MAK list) was used as the basis for the preparation and/or revision of this safety data sheet.

### 8.2 Exposure controls

**Appropriate engineering controls** No further data; see section 7.

### Individual protection measures, such as personal protective equipment

#### General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Provide adequate general ventilation and local process ventilation. Use local exhaust ventilation if necessary.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Use a moisturising skin cream after processing the product.

#### Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Filter P3.

#### Hand protection

Protective gloves.

The hands must be cleaned from the powder before putting on the gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the mixture.

#### Material of gloves

Nitrile impregnated cotton gloves complying with the standard EN 374-1.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye/face protection** Tightly sealed goggles

**Body protection:** Protective work clothing.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### General Information

<b>Colour:</b>	Grey
<b>Odour:</b>	Characteristic
<b>Odour threshold:</b>	Not determined.
<b>Melting point/freezing point:</b>	Undetermined.
<b>Boiling point or initial boiling point and boiling range</b>	Undetermined.
<b>Lower and upper explosion limit</b>	
<b>Lower:</b>	Not applicable

(Contd. on page 7)

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 18.08.2023

Version number 2 (replaces version 1)

Revision: 17.08.2023

**Trade name weberfloor 4670N Marine Base**

(Contd. of page 6)

<b>Upper:</b>	Not applicable
<b>Flash point:</b>	Not applicable
<b>Auto-ignition temperature:</b>	Not determined.
<b>Decomposition temperature:</b>	Not determined.
<b>pH at 20 °C</b>	11.5 In water
<b>Viscosity:</b>	
<b>Kinematic viscosity</b>	Not determined.
<b>dynamic:</b>	Not determined.
<b>Solubility</b>	
<b>Water:</b>	Hardens when in contact with water.
<b>Partition coefficient n-octanol/water (log value)</b>	Not determined.
<b>Vapour pressure:</b>	Not determined.
<b>Density and/or relative density</b>	
<b>Density:</b>	Not determined
<b>Bulk density at 20 °C:</b>	1700 kg/m <sup>3</sup> Not applicable.
<b>Vapour density</b>	Not determined.
<b>Particle characteristics</b>	
See section 3.	

<b>9.2 Other information</b>	None.
<b>Appearance:</b>	
<b>Form:</b>	Powder
<b>Important information on protection of health and environment, and on safety.</b>	
<b>Ignition temperature:</b>	Product is not self-igniting.
<b>Explosive properties:</b>	Product does not present an explosion hazard.
<b>Minimum ignition energy</b>	
<b>Solvent separation test:</b>	Not determined
<b>Solvent content:</b>	
<b>Organic solvents:</b>	0.0 %
<b>EU-VOC (%)</b>	0.0000 %
<b>EU-VOC (g/L)</b>	-0.0000 g/l
<b>Change in condition</b>	
<b>Softening point/range</b>	
<b>Oxidising properties</b>	Not determined.
<b>Evaporation rate</b>	Not determined.

**Information with regard to physical hazard**

<b>classes</b>	
<b>Explosives</b>	Void
<b>Flammable gases</b>	Void
<b>Aerosols</b>	Void
<b>Oxidising gases</b>	Void
<b>Gases under pressure</b>	Void
<b>Flammable liquids</b>	Void
<b>Flammable solids</b>	Void
<b>Self-reactive substances and mixtures</b>	Void
<b>Pyrophoric liquids</b>	Void
<b>Pyrophoric solids</b>	Void

(Contd. on page 8)



## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2023

Version number 2 (replaces version 1)

Revision: 17.08.2023

**Trade name weberfloor 4670N Marine Base**

(Contd. of page 7)

<b>Self-heating substances and mixtures</b>	Void
<b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
<b>Oxidising liquids</b>	Void
<b>Oxidising solids</b>	Void
<b>Organic peroxides</b>	Void
<b>Corrosive to metals</b>	Void
<b>Desensitised explosives</b>	Void

### SECTION 10: Stability and reactivity

**10.1 Reactivity** No further relevant information available.

**10.2 Chemical stability** Stable at recommended storage conditions

**Thermal decomposition / Conditions to be avoided:**

No decomposition if used according to specifications.

**10.3 Possibility of hazardous reactions**

Reacts with acids

Reacts with light alloys in the presence of moisture to form hydrogen

**10.4 Conditions to avoid**

Avoid water ingress/moisture during storage (the product will react with moisture and harden).

**10.5 Incompatible materials:** No further relevant information available.

**10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity** Based on available data, the classification criteria are not met.

**LD/LC50 values relevant for classification:**

Components	Type	Value	Species
<b>CAS: 65997-16-2 Cement, alumina, chemicals</b>			
Oral	LD50	>2,000 mg/kg	(Rat)
Dermal	LD50	>2,000 mg/kg	(Rat)
<b>CAS: 7778-18-9 calcium sulphate, different hydrate levels CaSO<sub>4</sub> x n H<sub>2</sub>O (n = 0; 1/2; 2)</b>			
Oral	LD50	>2,000 mg/kg	(Rat)
<b>CAS: 471-34-1 calcium carbonate</b>			
Oral	LD50	6,450 mg/kg	(Rat)
Dermal	LD50	6,450 mg/kg	(Rat)
<b>CAS: 65997-15-1 cement portland, grey</b>			
Dermal	LD50	>2,000 mg/kg	(Rabbit)

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/irritation** Causes serious eye damage.

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

(Contd. on page 9)



## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2023

Version number 2 (replaces version 1)

Revision: 17.08.2023

**Trade name weberfloor 4670N Marine Base**

(Contd. of page 8)

**STOT-single exposure** Based on available data, the classification criteria are not met.

**STOT-repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

### 11.2 Information on other hazards

#### Endocrine disrupting properties

None of the ingredients is listed.

## SECTION 12: Ecological information

### 12.1 Toxicity

**Aquatic toxicity:** Not classified as harmful to aquatic life

Type of test / Effective concentration / Method / Assessment	
<b>CAS: 65997-16-2 Cement, alumina, chemicals</b>	
LC50/96h	100 mg/l (Fish)
EC50/48h	5.4 mg/l (Daphnia magna)
EC50/72h	3.6 mg/l (Algae)
<b>CAS: 7778-18-9 calcium sulphate, different hydrate levels CaSO<sub>4</sub> x n H<sub>2</sub>O (n = 0; 1/2; 2)</b>	
LC50/48h	79-1,970 mg/l (Daphnia magna)
LC50/96h	79-2,980 mg/l (Fish)
EC50/72h	>79 mg/l (Selenastrum capricornutum (Green algae))
<b>CAS: 471-34-1 calcium carbonate</b>	
EC50/72h	14 mg/l (Algae)

**12.2 Persistence and degradability** No further relevant information available.

**Other information:** The product is not easily biodegradable.

**12.3 Bioaccumulative potential** No further relevant information available.

**12.4 Mobility in soil** No further relevant information available.

### 12.5 Results of PBT and vPvB assessment

**PBT:** Does not contain PBT substances.

**vPvB:** Does not contain vPvB substances.

### 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

**12.7 Other adverse effects** No further relevant information available.

### Remark:

The product contains substances which causes severe clouding in water

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

### Behaviour in sewage processing plants:

Type of test / Effective concentration / Method / Assessment	
<b>CAS: 65997-16-2 Cement, alumina, chemicals</b>	
EC 50 (3h)	1,000 mg/l (Activated sludge)
<b>CAS: 7778-18-9 calcium sulphate, different hydrate levels CaSO<sub>4</sub> x n H<sub>2</sub>O (n = 0; 1/2; 2)</b>	
EC 50 (3h)	>1,000 mg/l (Activated sludge)

(Contd. on page 10)



**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 18.08.2023

Version number 2 (replaces version 1)

Revision: 17.08.2023

**Trade name weberfloor 4670N Marine Base**

(Contd. of page 10)

For bulk product: shelf life 3 months starting from date on the Delivery note.

**Labelling according to Regulation (EC) No 1272/2008** cf. section 2

**Directive 2012/18/EU**

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

**REGULATION (EC) No 1907/2006 ANNEX XVII**

The marketing and use of cement is subject to a restriction on the content of soluble Cr (VI) (REACH Annex XVII Entry no. 47 Chromium VI compounds)

Conditions of restriction: 47

**DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

**REGULATION (EU) 2019/1148**

**Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

**Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

**Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

**Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

**Relevant phrases**

The following list of relevant hazard statements is the full text of hazard statements mentioned elsewhere in this safety data sheet (in particular in the section 3) and is reported as required by the Regulation (EC) No 1907/2006 (REACH), Annex II, and the following amendments (Regulation (EU) 2020/878). The statements mentioned here do not refer to the product itself, but refer to the individual ingredients in the products, and are provided for information.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

EUH203 Contains chromium (VI). May produce an allergic reaction.

**Classification according to Regulation (EC) No 1272/2008**

Skin corrosion/irritation	Skin irritation 2, H315. based on cement based mixtures in-vitro test results
Serious eye damage/irritation	Eye damage 1, H318. based on cement based mixtures in-vitro test results

(Contd. on page 12)

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2023

Version number 2 (replaces version 1)

Revision: 17.08.2023

**Trade name weberfloor 4670N Marine Base**

(Contd. of page 11)

**Department issuing SDS:** Technical department

**Contact:**

Line Holaker

+47 41 63 50 46

teknisk@weber-norge.no

**Version number of previous version: 1**

**Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

**\* Data compared to the previous version altered.**

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.

EUG