

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 18.08.2023

Version number 1

Revision: 05.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name weber.floor 4760N Komp.B

Safety data sheet no.: 49PX21430-b

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Epoxy coating

Hardening agent/ Curing agent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain Byggevarer as

Sandstuveien 68

Postboks 6211 Etterstad

0603 Oslo

Norway

Phone: +47 41 63 50 46

teknisk@weber-norge.no

1.4 Emergency telephone number:

GIFTINFORMASJONSSENTRALEN (Norwegian Poison Information Centre): +47 22 59 13 0

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS09 environment

Aquatic Acute 1 H400 Very toxic to aquatic life.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

EUG

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2023

Version number 1

Revision: 05.12.2022

Trade name weber.floor 4760N Komp.B

(Contd. of page 1)

Hazard pictograms

GHS05 GHS07 GHS09

Signal word Danger**Hazard-determining components of labelling:**

3-aminomethyl-3,5,5-trimethylcyclohexylamine

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine

m-phenylenebis(methylamine)

Benzyl alcohol

Hazard statements

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Does not contain PBT substances.**vPvB:** Does not contain vPvB substances.

SECTION 3: Composition/information on ingredients

3.2 Mixtures**Description:** Reaction resin curer based on amines and polyamines.**Dangerous components:**

CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38-xxxx	Benzyl alcohol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332	25-50%
CAS: 1226892-44-9 EC number: 629-765-4 Reg.nr.: 01-2119490750-36-xxxx	Fatty acids C18 unsat, reaction products with triethylenetetramine ⚠ Skin Corr. 1C, H314; Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); ⚠ Skin Sens. 1A, H317	10-20%

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2023

Version number 1

Revision: 05.12.2022

Trade name weber.floor 4760N Komp.B

(Contd. of page 2)

CAS: 2855-13-2 EINECS: 220-666-8 Index number: 612-067-00-9 Reg.nr.: 01-2119514687-32-xxxx	3-aminomethyl-3,5,5-trimethylcyclohexylamine ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Skin Sens. 1A, H317 ATE: LD50 oral: 1,030 mg/kg Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	10-20%
CAS: 38294-64-3 NLP: 500-101-4 Reg.nr.: 01-2119965165-33-xxxx	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318; ⚠ Skin Sens. 1, H317; Aquatic Chronic 3, H412	10-20%
CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50-xxxx	m-phenylenebis(methylamine) ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317; Aquatic Chronic 3, H412, EUH071	5-10%

SVHC Void**Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Immediately remove any clothing soiled by the product.

Remove the victim immediately from the danger area. If the patient is unwell consult a doctor and present this data sheet.

After inhalation

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

After swallowing Drink plenty of water and provide fresh air. Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.**For safety reasons unsuitable extinguishing agents** Water with full jet

5.2 Special hazards arising from the substance or mixture

Carbon monoxide (CO)

(Contd. on page 4)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 18.08.2023

Version number 1

Revision: 05.12.2022

Trade name weber.floor 4760N Komp.B

(Contd. of page 3)

Nitrogen oxides (NO_x)

5.3 Advice for firefighters

Protective equipment: Wear self-contained respiratory protective device.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Particular danger of slipping on leaked/spilled product.

Ensure adequate ventilation.

6.2 Environmental precautions:

The product must not get into watercourses
or into the soil.

Inform respective authorities in case of seepage into water course or sewage system.

Suppress gases/fumes/haze with water spray.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility:

Do not store together with acids.

Store away from foodstuffs.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from freezing.

Protect from heat and direct sunlight.

Recommended storage temperature: 5-30°C.

7.3 Specific end use(s) No further relevant information available.

EUG

(Contd. on page 5)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 18.08.2023

Version number 1

Revision: 05.12.2022

Trade name weber.floor 4760N Komp.B

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

DNELs		
CAS: 100-51-6 Benzyl alcohol		
Oral	Derived No Effect Level	4 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	8 mg/kgxday (worker systemic long term value) 4 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	22 mg/m ³ (worker systemic long term value) 5.4 mg/m ³ (consumer systemic long term value)
CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine		
Oral	Derived No Effect Level	0.3 mg/kgxday (consumer systemic long term value) 0.3 mg/kgxday (consumer systemic short term value)
Inhalative	Derived No Effect Level	0.073 mg/m ³ (worker local short term value) 0.073 mg/m ³ (worker local long term value)
CAS: 38294-64-3 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine		
Dermal	Derived No Effect Level	0.14 mg/kgxday (worker systemic long term value) 0.05 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	0.98 mg/m ³ (worker systemic long term value) 0.18 mg/m ³ (consumer systemic long term value)
CAS: 1477-55-0 m-phenylenebis(methylamine)		
Dermal	Derived No Effect Level	0.33 mg/kgxday (worker systemic long term value)
Inhalative	Derived No Effect Level	1.2 mg/m ³ (worker systemic long term value) 0.2 mg/m ³ (worker local long term value)

PNECs	
CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine	
Predicted No-Effect Concentration	0.06 mg/l (fresh water rating factor)
CAS: 1477-55-0 m-phenylenebis(methylamine)	
Predicted No-Effect Concentration	0.0094 mg/l (sea water rating factor) 0.094 mg/l (fresh water rating factor)

CAS No. / Designation of material / % / Type / Value / Unit	
CAS: 100-51-6 Benzyl alcohol	
AGW (Germany)	Long-term value: 22 mg/m ³ , 5 ppm 2(I);DFG, H, Y, 11
HTP (Finland)	Long-term value: 45 mg/m ³ , 10 ppm
CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine	
MAK (Germany)	als Dampf und Aerosol;vgl.Abschn.IIb
CAS: 1477-55-0 m-phenylenebis(methylamine)	
MAK (Germany)	als Dampf und Aerosol;vgl.Abschn.IV

(Contd. on page 6)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 18.08.2023

Version number 1

Revision: 05.12.2022

Trade name weber.floor 4760N Komp.B

(Contd. of page 5)

GV (Denmark)	Ceiling limit: 0.1 mg/m ³ , 0.02 ppm LH
TWA (Italy)	Ceiling limit: 0.1 mg/m ³ Cute
VLE (Portugal)	Ceiling limit: 0.1 mg/m ³ P; Irritação ocular, cutânea e GI
HTP (Finland)	Ceiling limit: 0.1 mg/m ³ iho

Additional information:

The applicable TRGS 900 (MAK list) was used as the basis for the preparation and/or revision of this safety data sheet.

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Do not eat, drink, smoke or sniff while working.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Use a moisturising skin cream after processing the product.

Avoid contact with the eyes and skin.

Respiratory protection:

Not necessary if room is well-ventilated.

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Short term filter device:

Filter A2

Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

Recommended thickness of the material: ≥ (Butyl) 0.7mm; (NBR) 0.4 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

Breakthrough time: > 480 min

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Tightly sealed goggles

Body protection: Protective work clothing.

EUG

(Contd. on page 7)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 18.08.2023

Version number 1

Revision: 05.12.2022

Trade name weber.floor 4760N Komp.B

(Contd. of page 6)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Colour:	Yellowish
Odour:	Amine-like
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling range	260 °C
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
Flash point:	110 °C
Auto-ignition temperature:	230 °C
pH	Not applicable.
Viscosity:	
Kinematic viscosity	Not determined.
dynamic at 20 °C:	100-200 mPas
Solubility	
Water:	Not miscible or difficult to mix
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C:	1.02 g/cm ³
Bulk density:	Not applicable.
Vapour density	Not determined.

9.2 Other information

Appearance:	No further relevant information available.
Form:	Pasty
Important information on protection of health and environment, and on safety.	
Ignition temperature:	Product is not self-igniting.
Explosive properties:	Product does not present an explosion hazard.
EU-VOC (%)	26.9000 %
Change in condition	
Softening point/range	
Oxidising properties	Not determined.
Evaporation rate	Not determined.

Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void

(Contd. on page 8)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 18.08.2023

Version number 1

Revision: 05.12.2022

Trade name weber.floor 4760N Komp.B

(Contd. of page 7)

Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / Conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

Exothermic polymerisation.

Reacts with alcohols, amines, aqueous acids and alkalis

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

Poisonous gases/vapours

Corrosive gases/vapours

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Components	Type	Value	Species
CAS: 100-51-6 Benzyl alcohol			
Oral	LD50	1,620 mg/kg	(Rat)
Dermal	LD50	>2,000 mg/kg	(Rabbit)
Inhalative	LC50/4 h	>4.178 mg/l	(Rat)
CAS: 1226892-44-9 Fatty acids C18 unsat, reaction products with triethylenetetramine			
Oral	LD50	>2,000 mg/kg	(Rat)
CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine			
Oral	LD50	1,030 mg/kg	(ATE)
		1,030 mg/kg	(Rat)
Dermal	LD50	>2,000 mg/kg	(Rat)
CAS: 1477-55-0 m-phenylenebis(methylamine)			
Oral	LD50	930 mg/kg	(Rat)
Dermal	LD50	>3,100 mg/kg	(Rabbit)

(Contd. on page 9)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 18.08.2023

Version number 1

Revision: 05.12.2022

Trade name weber.floor 4760N Komp.B

(Contd. of page 8)

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Harmful to aquatic life with long lasting effects.

Type of test / Effective concentration / Method / Assessment

CAS: 100-51-6 Benzyl alcohol

LC50/48h	260 mg/l (Daphnia magna) 645 mg/l (Leuciscus idus (Orfe))
LC50/96h	10 mg/l (Lepomis macrochirus (Sunfish)) 460 mg/l (Pimephales promelas (Minnow))
EC50/24h	400 mg/l (Daphnia magna)
EC50/48h	230 mg/l (Daphnia magna)
EC50/96h	400 mg/l (Daphnia magna) 640 mg/l (Scenedesmus subspicatus (Algae))
EC50/72h	770 mg/l (Algae)
NOEC (72h)	310 mg/l (Algae)
NOEC (21d)	51-66 mg/l (Daphnia magna)
EC 10	400 mg/l (Pseudomonas putida (Bacteria))

CAS: 1226892-44-9 Fatty acids C18 unsat, reaction products with triethylenetetramine

LC50/96h	0.19 mg/l (Fish)
EC50/48h	0.18 mg/l (Daphnia magna)
EC50/72h	0.505 mg/l (Algae)
NOEC (21d)	0.27 mg/l (Daphnia magna)

CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

LC50/48h	388 mg/l (Daphnia magna)
LC50/96h	110 mg/l (Brachydanio rerio (zebra danio))
EC50/24h	27 mg/l (Daphnia magna)
EC50/48h	23 mg/l (Daphnia magna)

(Contd. on page 10)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 18.08.2023

Version number 1

Revision: 05.12.2022

Trade name weber.floor 4760N Komp.B

(Contd. of page 9)

EC50/72h	50 mg/l (Scenedesmus subspicatus (Algae))
NOEC (21d)	3 mg/l (Daphnia magna)
EC 10/18h	11.2 mg/l (Algae)
CAS: 1477-55-0 m-phenylenebis(methylamine)	
LC50/96h	87.6 mg/l (Oryzias latipes (Japanese medaka))
EC50/48h	15.2 mg/l (Daphnia magna)
EC50/72h	20.3 mg/l (Scenedesmus subspicatus (Algae))

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential

CAS: 100-51-6 Benzyl alcohol

EBAB | 1.05 log Pow (Bioaccumulation)

CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

EBAB | 0.99 log Pow

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Remark:

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

Harmful to fish

Behaviour in sewage processing plants:

Type of test / Effective concentration / Method / Assessment	
CAS: 100-51-6 Benzyl alcohol	
EC 50 (3h)	79 mg/l (Scenedesmus quadricauda (Algae))
CAS: 1226892-44-9 Fatty acids C18 unsat, reaction products with triethylenetetramine	
EC 50 (3h)	175 mg/l (Activated sludge)

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

After mixing with the resin component pour a partial amount back into the curing agent barrel, stir well and pour the mass back once more. Cured epoxy resin products are waste that requires no particular supervision and can as a rule be disposed of as commercial waste that is similar to household rubbish.

(Contd. on page 11)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2023

Version number 1

Revision: 05.12.2022

Trade name weber.floor 4760N Komp.B

(Contd. of page 10)

European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances

Uncleaned packaging:
Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Recommended cleaning agent: Water, if necessary together with cleansing agents.

SECTION 14: Transport information

**14.1 UN number or ID number
ADR, IMDG, IATA**

UN2735

**14.2 UN proper shipping name
ADR**

2735 AMINES, LIQUID, CORROSIVE, N.O.S. (ISOPHORONEDIAMINE), ENVIRONMENTALLY HAZARDOUS

IMDG, IATA

AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine), 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with ethylenediamine)

14.3 Transport hazard class(es)
ADR

**Class
Label**

 8 (C7) Corrosive substances.
8

IMDG, IATA

**Class
Label**

 8 Corrosive substances.
8

**14.4 Packing group
ADR, IMDG, IATA**

II

14.5 Environmental hazards:
Marine pollutant:

No

14.6 Special precautions for user

Warning: Corrosive substances.

Hazard identification number (Kemler code): 80

EMS Number:

F-A,S-B

Segregation groups

(SGG18) Alkalis

(Contd. on page 12)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 18.08.2023

Version number 1

Revision: 05.12.2022

Trade name weber.floor 4760N Komp.B

(Contd. of page 11)

Stowage Category	A
Segregation Code	SG35 Stow "separated from" SGG1-acids
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	E
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
IATA	
Packing instructions Passenger:	
Packing instructions cargo:	
UN "Model Regulation":	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (ISOPHORONEDIAMINE), 8, II, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Regulation (EC) No 1272/2008 (CLP)

Regulation (EU) 2020/878 (amending REACH Annex II on the compilation of safety data sheets)

Labelling according to Regulation (EC) No 1272/2008 cf. section 2

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category E1 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

(Contd. on page 13)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 18.08.2023

Version number 1

Revision: 05.12.2022

Trade name weber.floor 4760N Komp.B

(Contd. of page 12)

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

National regulations

Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

Relevant phrases

The following list of relevant hazard statements is the full text of hazard statements mentioned elsewhere in this safety data sheet (in particular in the section 3) and is reported as required by the Regulation (EC) No 1907/2006 (REACH), Annex II, and the following amendments (Regulation (EU) 2020/878). The statements mentioned here do not refer to the product itself, but refer to the individual ingredients in the products, and are provided for information.

- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH071 Corrosive to the respiratory tract.

Classification according to Regulation (EC) No 1272/2008

Skin corrosion/irritation Serious eye damage/irritation Skin sensitisation Hazardous to the aquatic environment - short-term (acute) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	Expert judgement

Department issuing SDS: Technical department

(Contd. on page 14)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 18.08.2023

Version number 1

Revision: 05.12.2022

Trade name weber.floor 4760N Komp.B

(Contd. of page 13)

Contact:

Line Holaker

+47 41 63 50 46

teknisk@weber-norge.no

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the previous version altered.**

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.