

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Certificate no.:
MEDB00004NY
Revision No:
1

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED), issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Authority. This Certificate is issued by DNV AS under the authority of the Government of Norway.

This is to certify:

that the **Primary deck coverings**

with type designation(s)
weberfloor 4769N Epoxy Mortar

issued to

SAINT-GOBAIN BYGGEVARER AS
Oslo, Norway

is found to comply with the requirements in the following Regulations/Standards:

Regulation (EU) 2023/1667,

item No. MED/3.1. SOLAS 74 as amended, Regulation II-2/4, II-2/6 & X/3, 2000 HSC Code 7 and IMO 2010 FTP Code


Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2028-12-06**.

Issued at **Høvik** on **2023-12-05**

DNV local unit:
East & South Norway CMC

Approval Engineer:
Karolina Kusmider



Notified Body
No.: **0575**

for **DNV AS**

.....
Sverre Olav Bergli
Head of Notified Body

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F), as allowed by the "Agreement between the United States of America and the EEA EFTA states on the mutual recognition of Certificates of Conformity for Marine Equipment" signed 17 October 2005, and amended by Decision No 1/2023 dated August 21st, 2023.



The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU.

This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV AS of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled.

Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Product description

“weberfloor 4769N Epoxy Mortar”

Consists of an epoxy resin primer (weberfloor 4760N Epoxy Primer / weberfloor 4762N Epoxy Primer), an epoxy resin mortar (weberfloor 4769N Epoxy Mortar) mixed with weberfloor mortar filler combined with sand quartz used as bonding layer.

Nominal thickness: 11.1 mm

Nominal density: 2000 kg/m³

The layer structure is described as follows from bottom to top.

1. weberfloor 4760N Epoxy Primer / weberfloor 4762N Epoxy Primer
Applied thickness: 0.3 mm / 0.1-0.2 mm
Density: 1.08 kg/L / 1800kg/m³ (dried)
2. weberfloor quartz sand
Applied thickness: 0.3-0.8 mm
Density: 2000 kg/m³
3. weberfloor 4769N Epoxy Mortar + weberfloor mortar filler
Applied thickness: 10 mm
Density: 2000 kg/m³

Application/Limitation

Primary deck covering, not generating excessive quantities of smoke nor toxic products in fire.

weberfloor 4760N Epoxy Primer / weberfloor 4762N Epoxy Primer

Approved colour: Transparent, yellow / transparent

Max. organic content: 100% / 22%

weberfloor 4769N Epoxy Mortar + weberfloor mortar filler

Approved colour: Natural

Max.organic content: 7.7%

The product may be applied over any steel or non-combustible material.

The product may also be used as floor covering in accordance with IMO 2010 FTP Code Part 5 Appendix 4 paragraph 4.9.2.

Not to be used as an integrated part of horizontal class A division unless tested as such.

Each product is to be supplied with its manual for installation, use and maintenance.

Type Examination documentation

Test report No. 8P06770-1 dated 04 October 2018 from RISE, Research Institutes of Sweden, Borås, Sweden.

Test report No. 8P06770 dated 12 September 2018 from RISE, Research Institutes of Sweden, Borås, Sweden.

Test Report No. O100352-127178-8rev1 dated 17 June 2021 from RISE, Research Institutes of Sweden, Borås, Sweden.

Assessment Report No. O100611-1105880 dated 25 February 2022 from RISE, Research Institutes of Sweden, Borås, Sweden.

Tests carried out

Tested according to IMO 2010 FTP Code Annex 1, Part 5 and Part 2.

Marking of product

The product is to be marked with name and address of manufacturer, type designation, the MED Mark of Conformity and USCG Approval Number if applicable (see first page).