

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Certificate No:
MEDB00008BR

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED), issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Authority. This Certificate is issued by DNV AS under the authority of the Government of Norway.

This is to certify:

That the Primary deck coverings

with type designation(s)
Weber Marine Coloured Sand Coating

Issued to
SAINT-GOBAIN BYGGEVARER AS
Oslo, Norway

is found to comply with the requirements in the following Regulations/Standards:
Regulation (EU) 2022/1157,
item No. MED/3.1. SOLAS 74 as amended, Regulation II-2/4, II-2/6 & X/3, 2000 HSC Code 7 and IMO 2010 FTP Code


Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2028-03-09**.

Issued at **Høvik** on **2023-03-10**

DNV local unit:
East & South Norway CMC

Approval Engineer:
Thorvald Furuseth



Notified Body
No.: **0575**



for **DNV AS**

Digitally Signed By:
Øyvind Hoff
Location: DNV Høvik, Norway
on behalf of

Sverre Olav Bergli
Head of Notified Body

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F), as allowed by the "Agreement between the United States of America and the EEA EFTA states on the mutual recognition of Certificates of Conformity for Marine Equipment" signed 17 October 2005, and amended by Decision No 1/2019 dated February 22nd, 2019.



The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU.

This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV AS of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled.

Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Product description

“Weber Marine Coloured Sand Coating”

Consist of weberfloor 4762 N Epoxy primer, weberfloor 4761 N Epoxy coating, weberfloor colored quartz sand and weberfloor 4773 N PU Clear Top Coat.

Max. approved thickness 3 mm

The layer structure is described as follows from bottom to top.

Layer construction:

weberfloor 4762 N Epoxy primer + 10% water

Applied thickness: 0.15 mm
Applied quantity: 0.2 kg/m²
Density: 1.80 kg/L / 1800 kg/m³ (dried)
Maximum organic content: 22%
Approved colour: Transparent/ uncoloured

weberfloor 4761 N Epoxy coating

Applied thickness: 0.9 mm
Applied quantity: 1.2 kg/m²
Density: 1.31 kg/L / 1310 kg/m³ (dried)
Maximum organic content: 66%
Approved colour: RAL 9005 (Black/dark)

weberfloor colored quartz sand

Applied thickness: -
Applied quantity: 3.0 kg/m²
Density: 2.65 kg/L / 2650 kg/m³ (dried)
Maximum organic content: 5%
Approved colour: Black

weberfloor 4773 N PU Clear Top Coat

Applied thickness: 0.5 mm
Applied quantity: 0.5 kg/m²
Density: 1.10 kg/L / 1100 kg/m³ (dried)
Maximum organic content: 100%
Approved colour: Transparent/ uncoloured

For further details see test report as referred below

Application/Limitation

Primary deck covering, not generating excessive quantities of smoke nor toxic products in fire.

The product may also be used as floor covering in accordance with IMO 2010 FTP code Part 5 Appendix 4 paragraph 4.9.2.

The product may be applied over any steel or non-combustible material.

Not to be used as an integrated part of horizontal class A division unless tested as such.

Each product is to be supplied with its manual for installation, use and maintenance.

Type Examination documentation

Test report No. 20210948/01.1 dated 16th of December 2021 from MPA Dresden GmbH, Freiberg, Germany.

Test report No. 2021-1502 dated 9th of November 2021 from Brandhaus Rhein-Main, Frankfurt, Germany.



Job Id: **344.1-012584-1**
Certificate No: **MEDB00008BR**

Tests carried out

Tested according to IMO 2010 FTP Code Part 5 and 2.

Marking of product

The product or packing is to be marked with name and address of manufacturer, type designation, MED Mark of Conformity and USCG approval if applicable (see first page).